

Model 780

Current Transformer Window Diameter 6.50"

Application

Relaying and metering.

Frequency

50-400 Hz.

Insulation Level

0.6 kV, BIL 10 kV full wave.

Continuous Thermal Current Rating Factor

50:5-1,200:5 & 2,000:5
2.0 at 30 °C. amb., 1.5 at 55 °C. amb.

1,500:5-1600:5, 2,500:5-3,500:5
1.5 at 30 °C. amb., 1.33 at 55 °C. amb.

4,000:5-5,000:5 1.0 at 30 °C. amb.,

6,000:5 0.8 30 °C. amb.

Secondary terminals are brass screws
No.10-32 with one flatwasher,
lockwasher and regular nut.

Approximate weight 30 lbs.
Excitation data available upon request.



REGULATORY AGENCY APPROVALS



Manufactured to meet the requirements of ANSI/IEEE C57.13.
Classified by U.L. in accordance with IEC 44-1

Model 780

Catalog Number	Current Ratio	Relay Class	ANSI Metering Class at 60 Hz				
			B0.1	B0.2	B0.5	B0.9	B1.8
780-500	50:5	—	4.8	—	—	—	—
780-750	75:5	C10	4.8	4.8	—	—	—
780-101	100:5	C10	1.2	2.4	4.8	—	—
780-151	150:5*	C20	0.6	1.2	2.4	2.4	4.8
780-201	200:5*	C20	0.6	0.6	1.2	2.4	4.8
780-251	250:5*	C20	0.6	0.6	0.6	1.2	2.4
780-301	300:5*	C20	0.3	0.6	0.6	1.2	2.4
780-401	400:5*	C50	0.3	0.3	0.6	0.6	1.2
780-501	500:5*	C50	0.3	0.3	0.3	0.6	0.6
780-601	600:5*	C100	0.3	0.3	0.3	0.3	0.6
780-801	800:5*	C100	0.3	0.3	0.3	0.3	0.6
780-102	1,000:5*	C100	0.3	0.3	0.3	0.3	0.3
780-122	1,200:5*	C200	0.3	0.3	0.3	0.3	0.3
780-152	1,500:5*	C200	0.3	0.3	0.3	0.3	0.3
780-162	1,600:5*	C200	0.3	0.3	0.3	0.3	0.3
780-202	2,000:5*	C200	0.3	0.3	0.3	0.3	0.3
780-252	2,500:5*	C200	0.3	0.3	0.3	0.3	0.3
780-302	3,000:5*	C200	0.3	0.3	0.3	0.3	0.3
780-322	3,200:5*	C200	0.3	0.3	0.3	0.3	0.3
780-352	3,500:5*	C200	0.3	0.3	0.3	0.3	0.3
780-402	4,000:5*	C200	0.3	0.3	0.3	0.3	0.3
780-502	5,000:5	C200	0.3	0.3	0.3	0.3	0.3
780-602	6,000:5*	C200	0.3	0.3	0.3	0.3	0.3

(*) Approved for revenue metering by Industry Canada No. AE-0656



